

MSA 1.8M Kernmantle Energy Absorbing Lanyard



The MSA lanyards are available in web and kernmantel rope configurations with a variety of connectors. Energy-absorbing lanyards provide a means of connection between the fall arrest attachment of MSA full body harnesses and a qualified anchorage point. The energy absorber keeps fall arrest forces below 6 kN.

- Single leg configuration, twin-leg options also available
- Leading edge approved for use in leading edge application
- Cross stitch and a strong transparent covering sleeve to protect the ends and makes the stitches visible for easy inspection
- Abrasion resistant thimble at the end of the loops to prevent the rope from being damaged by the metallic contact of the connector
- A colour tracer strand that loses its colour in due course of time showing that the lanyard is now unfit for further use
- 11mm Nylon Kernmantel rope
- Galvanized alloy steel twist-lock carabiner
- The Carabiner has a minimum breaking strength of 23kN with a gate opening of 60mm
- Aluminum Alloy Scaffolding hook
- The Scaffolding hook has a minimum breaking strength of 23 kN with a gate opening of 16 mm
- Maximum arrest force of 6kN
- Conforms to EN 352:2002 Personal protective equipment against falls from a height. Energy absorbers



Product Code

MSA10185614

Available in Sizes

1.8M

Available in Colours



Chrome
MSA10185614

